## IN THE CLAIMS

The following is a complete set of claims pending with this response. This complete set of claims have not been altered subsequent to the last Amendment and Reply.

- 1. (Original) A method used for provisioning an access key to receive broadcast services in a terminal storing a private key comprising:
  - distributing a public key corresponding to the private key; receiving a secret key encrypted by the public key; decrypting the secret key by the private key; receiving the access key encrypted by the secret key; and decrypting the access key by the secret key.
- 2. (Original) The method of claim 1, wherein the secret key is a registration key.
- 3. (Original) The method of claim 1, wherein the secret key is a temporary key.
- 4. (Original) The method of claim 1, further comprising: deriving a short key based on the access key; receiving encrypted broadcast content; and decrypting the encrypted broadcast content using the short key.
- 5. (Previously Presented) A method used for provisioning a broadcast access key to receive broadcast services in a terminal storing a private key comprising:

  distributing a public key corresponding to the private key;

  receiving the broadcast access key encrypted by the public key; and decrypting the broadcast access key by the private key.
- 6. (Cancelled)
- 7. (Cancelled)

- 8. (Previously Presented) The method of claim 5, further comprising: deriving a short key based on the broadcast access key; receiving encrypted broadcast content; and decrypting the encrypted broadcast content using the short key.
- 9. (Original) A method used for provisioning an access key to receive broadcast services in a terminal storing a secret key comprising:

receiving a public key corresponding to a private key; encrypting the secret key with the public key; sending the encrypted secret key; receiving the access key encrypted by the secret key; and decrypting the access key by the secret key.

- 10. (Original) The method of claim 9, wherein the secret key is a registration key.
- 11. (Original) The method of claim 9, wherein the secret key is a temporary key.
- 12. (Original) The method of claim 9, further comprising: deriving a short key based on the access key; receiving encrypted broadcast content; and decrypting the encrypted broadcast content using the short key.
- 13. (Previously Presented). A method used for distributing an access key to provide broadcast services from a content provider comprising:

receiving a public key corresponding to a private key; encrypting a secret key using the public key; sending the encrypted secret key; encrypting the access key using the secret key; and sending the encrypted access key.

14. (Original) The method of claim 13, wherein the secret key is a registration key.

- 15. (Original) The method of claim 13, wherein the secret key is a temporary key.
- 16. (Previously Presented) A method used for distributing a broadcast access key to provide broadcast services from a content provider comprising:

  receiving a public key corresponding to a private key;
  encrypting the broadcast access key using the pubic key; and sending the encrypted broadcast access key.
- 17. (Cancelled)
- 18. (Cancelled)
- 19. (Original) A method used for distributing an access key to provide broadcast services from a content provider having stored a private key comprising:

distributing a public key corresponding to the private key; receiving a secret key encrypted by the public key; decrypting the secret key using the private key; encrypting the access key using the secret key; and sending the encrypted access key.

- 20. (Original) The method of claim 19, wherein the secret key is a registration key.
- 21. (Original) The method of claim 19, wherein the secret key is a temporary key.
- 22. (Original) Apparatus for provisioning an access key to receive broadcast services in a terminal storing a private key comprising:

means for distributing a public key corresponding to the private key; means for receiving a secret key encrypted by the public key; means for decrypting the secret key by the private key; means for receiving the access key encrypted by the secret key; and

means for decrypting the access key by the secret key.

- 23. (Original) The apparatus of claim 22, wherein the secret key is a registration key.
- 24. (Original) The apparatus of claim 22, wherein the secret key is a temporary key.
- 25. (Previously Presented) Apparatus for provisioning a broadcast access key to receive broadcast services in a terminal storing a private key comprising:

  means for distributing a public key corresponding to the private key;

  means for receiving the broadcast access key encrypted by the public key; and means for decrypting the broadcast access key by the private key.
- 26. (Cancelled)
- 27. (Cancelled)
- 28. (Original) Apparatus for provisioning an access key to receive broadcast services in a terminal storing a secret key comprising:

means for receiving a public key corresponding to a private key; means for encrypting the secret key with the public key; means for sending the encrypted secret key; means for receiving the access key encrypted by the secret key; and means for decrypting the access key by the secret key.

- 29. (Original) The apparatus of claim 28, wherein the secret key is a registration key.
- 30. (Original) The apparatus of claim 28, wherein the secret key is a temporary key.
- 31. (Previously Presented) Apparatus for distributing an access key to provide broadcast services from a content provider comprising:

  means for receiving a public key corresponding to a private key;

means for encrypting a secret key using the public key; means for sending the encrypted secret key; means for encrypting the access key using the secret key; and means for sending the encrypted access key.

- 32. (Original) The apparatus of claim 31, wherein the secret key is a registration key.
- 33. (Original) The apparatus of claim 31, wherein the secret key is a temporary key.
- 34. (Currently Presented) Apparatus for distributing a broadcast access key to provide broadcast services from a content provider comprising:

means for receiving a public key corresponding to a private key; means for encrypting the broadcast access key using the public key; and means for sending the encrypted broadcast access key.

- 35. (Cancelled)
- 36. (Cancelled)
- 37. (Original) Apparatus for distributing an access key to provide broadcast services from a content provider having stored a private key comprising:

means for distributing a public key corresponding to the private key; means for receiving a secret key encrypted by the public key; means for decrypting the secret key using the private key; means for encrypting the access key using the secret key; and means for sending the encrypted access key.

- 38. (Original) The apparatus of claim 37, wherein the secret key is a registration key.
- 39. (Original) The apparatus of claim 37, wherein the secret key is a temporary key.

- 40. (Original) Machine readable medium used for provisioning an access key to receive broadcast services in a terminal storing a private key comprising:
  - codes for distributing a public key corresponding to the private key; codes for receiving a secret key encrypted by the public key; codes for decrypting the secret key by the private key; codes for receiving the access key encrypted by the secret key; and codes for decrypting the access key by the secret key.
- 41. (Original) The medium of claim 40, wherein the secret key is a registration key.
- 42. (Original) The medium of claim 40, wherein the secret key is a temporary key.
- 43. (Previously Presented) Machine readable medium used for provisioning a broadcast access key to receive broadcast services in a terminal storing a private key comprising: codes for distributing a public key corresponding to the private key; codes for receiving the broadcast access key encrypted by the public key; and codes for decrypting the broadcast access key by the private key.
- 44. (Cancelled)
- 45. (Cancelled)
- 46. (Original) Machine readable medium used for provisioning an access key to receive broadcast services in a terminal storing a secret key comprising:

codes for receiving a public key corresponding to a private key; codes for encrypting the secret key with the public key; codes for sending the encrypted secret key; codes for receiving the access key encrypted by the secret key; and codes for decrypting the access key by the secret key.

47. (Original) The medium of claim 46, wherein the secret key is a registration key.

- 48. (Original) The medium of claim 46, wherein the secret key is a temporary key.
- 49. (Previously Presented) Machine readable medium used for distributing an access key to provide broadcast services from a content provider comprising:

  codes for receiving a public key corresponding to a private key;

  codes for encrypting a secret key using the public key;

  codes for sending the encrypted secret key;

  codes for encrypting the access key using the secret key; and

  codes for sending the encrypted access key.
- 50. (Original) The medium of claim 49, wherein the secret key is a registration key.
- 51. (Original) The medium of claim 49, wherein the secret key is a temporary key.
- 52. (Previously Presented) Machine readable medium used for distributing a broadcast access key to provide broadcast services from a content provider comprising:

  codes for receiving a public key corresponding to a private key;

  codes for encrypting the broadcast access key using the public key; and codes for sending the encrypted broadcast access key.
- 53. (Cancelled)
- 54. (Cancelled)
- 55. (Original) Machine readable medium for distributing an access key to provide broadcast services from a content provider having stored a private key comprising: codes for distributing a public key corresponding to the private key; codes for receiving a secret key encrypted by the public key; codes for decrypting the secret key using the private key; codes for encrypting the access key using the secret key; and

codes for sending the encrypted access key.

- 56. (Original) The medium of claim 55, wherein the secret key is a registration key.
- 57. (Original) The medium of claim 55, wherein the secret key is a temporary key.
- 58. (New) A processor used for provisioning an access key to receive broadcast services in a terminal storing a private key, the processor configured to control:

distributing a public key corresponding to the private key; receiving a secret key encrypted by the public key; decrypting the secret key by the private key; receiving the access key encrypted by the secret key; and decrypting the access key by the secret key.

- 59. (New) The processor of claim 58, further configured to control: deriving a short key based on the access key; receiving encrypted broadcast content; and decrypting the encrypted broadcast content using the short key.
- 60. (New) A processor used for provisioning a broadcast access key to receive broadcast services in a User Identification Module storing a private key, the processor configured to control:

distributing a public key corresponding to the private key; receiving the broadcast access key encrypted by the public key; and decrypting the broadcast access key by the private key.

61. (New) The processor of claim 60, further configured to control:
deriving a short key based on the broadcast access key;
receiving encrypted broadcast content; and
decrypting the encrypted broadcast content using the short key.

62. (New) A processor used for provisioning an access key to receive broadcast services in a terminal storing a secret key, the processor configured to control:

receiving a public key corresponding to a private key; encrypting the secret key with the public key; sending the encrypted secret key; receiving the access key encrypted by the secret key; and decrypting the access key by the secret key.

63. (New) The processor of claim 62, further configured to control: deriving a short key based on the access key; receiving encrypted broadcast content; and decrypting the encrypted broadcast content using the short key.